








規格表 SPECIFICATIONS

型號		MODEL		Unit	HG-200	HG-250	HG-380	HG-470
盤面直徑		Disk size		mm	Ø200	Ø250	Ø380	Ø470
盤面中心孔直徑		Disk center hole diameter		mm	Ø16H7	Ø16H7	Ø30H7	Ø100H7
底部到盤面高度 (臥式使用)		Height from bottom to disk surface (Horizontal use)		mm	215	200	240	240
盤面T型槽寬度		T-slot width		mm	-	-	-	-
導鍵寬度		Guide key width		mm	-	18h7	-	-
最小設定角度		Minimum setting angle		deg.	5°	5°	1° or 5°	1° or 5°
分割精度		Index accuracy		sec.	±4	±4	±4	±4
重複精度				sec.	±1	±1	±1	±1
鎖緊方式	油壓	Clamping method	Hydraulic	kg/cm ²	35	35	35	35
鎖緊扭矩		Clamping torque		N.m	1250	1500	2000	2500
伺服馬達型號	FANUC	Servo motor model	FANUC	-	α 4if / β 8is	α 4if / β 8is	α 8 / β 12	α 8 / β 12
	三菱		MITSUBISHI	-	HF-154S	HF-154S	HF-154S	HF-154S
齒數比		Gear ratio		-	1 : 75	1 : 120	1 : 120	1 : 120
最高轉速 (馬達3000 rpm)		Maximum speed (Motor 3000 rpm)		rpm	40	25	25	25
容許負載容量	臥式	Allowable load capacity	Horizontal	kg	250	300	350	350
容許切削力 (鎖緊狀態)	F	Allowable cutting force (Clamped)	F	N.m	1000	1500	2000	2000
	F x L		F x L	N.m	2500	3000	4000	4000
蝸輪容許扭矩		Allowable torque of worm gear		N.m	230	480	750	750
容許慣性	$J = \frac{W \cdot D^2}{8}$	Allowable	$J = \frac{W \cdot D^2}{8}$	kg.m ²	1.25	2.34	6.3	9.7
轉台重量 (不含馬達)		Table weight (without motor)		kg	71	99	232	272

本公司保留產品規格尺寸，設計特性變更之權利，恕不另行通知。 All specifications, design and characteristics shown in this catalogue are subject to change without prior notice.